


Servo amplifier

mcDSA-FE55-Modul

Article number: 1516050



Picture similar

Technical data

Supply voltages		Incremental encoder	
Electronic supply voltage Ue* ¹	9..30 V	Type	incremental
Electronic current consumption@ Ue=24V* ²	typ. 40 mA	Signals	A,/A,B,/B,Inx
Power supply voltage Up* ³	9..60 V	Max. frequency (per channel)	500 kHz
Output current		Input voltage	0..5 V
Max. output current	50 A	Signal type	differential, open collector, single ended
Continuous output current @ Up=24V* ⁴	11.5 A	Hall sensors	
Continuous output current @ Up=60V* ⁵	8.5 A	Signals	H1,H2,H3
PWM		Max. frequency (per channel)	10 kHz
PWM frequency	32 kHz	Input voltage	0..5 V
Commutation type	Field Oriented Control	Signal type	open collector, single ended
Mechanical		Digital inputs	
Size LxWxH	70 x 50 x 19 mm	Number - digital inputs	8 (Din0..7)
Weight	50 g	Low voltage	0..5 V
Environment		High voltage	8..30 V
Protection class	IP00	Digital outputs	
Ambient temperature (operation)	-40..70 °C	Number	4 (Dout0..3)
Ambient temperature (storage)	-40..85 °C	Continuous output current	0..3 A
Rel. humidity (non-condensing)	5..90 %	Load Dout0..2	resistive, low inductive
CAN bus		Load Dout3	resistive, inductive
Protocol	DS301	Output voltage	Electronic supply voltage Ue
Device profile	DS402	Signal type	positive switching
Max. baudrate	1 Mbit/s	Analog inputs	
CAN specification	2.0B	Number	3 (Ain0..2)
Galvanically isolated	no	Signal type - Ain0..1	+/- 10 V, 12 Bit, differential
Sensor supply (Encoder/Hall)		Signal type - Ain2 / PT1000	0..5 V, 12 Bit, single ended / PT1000
Output voltage	5 V		
Max. output current	0.2 A		

*¹ No reverse polarity protection, the destruction limit is at overvoltage of >= 33V or short-term peak voltage of 37V < 1s*² power amplifier switched off, 5V output (sensor supply) is free*³ No reverse polarity protection, the destruction limit is at overvoltage of >= 80V*⁴ connector cable with max. possible cable cross-section, PWM frequency 32 kHz, ambient temperature 40 °C (t > 40 °C derating), RMS current: 11.5 A → 9.4 Aeff no guarantee, since value is determined empirical, please consider the application notes to determine the continuous current*⁵ connector cable with max. possible cable cross-section, PWM frequency 32 kHz, ambient temperature 40 °C (t > 40 °C derating), RMS current: 8.5 A → 6.9 Aeff no guarantee, since value is determined empirical, please consider the application notes to determine the continuous current

Additional technical data are available in mcManual.



miControl® GmbH

Chausseestraße 34


14979 Großbeeren (bei Berlin)

Copyright 2025 by miControl® - Modifications and errors excepted

mcDSA-FE55-Modul - PV1.14.00.07 / DV1.00.00.00

Web: www.miControl.de e-mail: info@miControl.de Tel.: +49 (3379) 312 59-0 Fax: +49 (3379) 312 59-19

Scheme



©2022 by miControl

Terminal assignment

X1	Supply	
1	FE	Functional earth
2	FE	Functional earth
3	+Up	Power supply voltage
4	+Up	Power supply voltage
5	+Up	Power supply voltage
6	+Up	Power supply voltage
7	GND	Ground for power supply voltage
8	GND	Ground for power supply voltage
9	GND	Ground for power supply voltage
10	GND	Ground for power supply voltage
11	+Ue24V	Electronic supply voltage
12	+Ue24V	Electronic supply voltage
13	GND	Ground for electronic supply voltage
14	GND	Ground for electronic supply voltage
15	GND	Ground for electronic supply voltage
16	GND	Ground for electronic supply voltage
X2	Analog inputs	
1	+Ain0	Analog input 0, plus
2	-Ain0	Analog input 0, minus
3	+Ain1	Analog input 1, plus
4	-Ain1	Analog input 1, minus
5	Ain2	Analog Input 2 (5V) / PT1000
X3	CAN bus	
1	CAN Hi	CAN High
2	CAN Lo	CAN Low
3	res.	Reserved
X4	Digital inputs/outputs	
1	res.	Reserved
2	Din0	Digital input 0
3	Din1	Digital input 1
4	Din2	Digital input 2
5	Din3	Digital input 3
6	Din4	Digital input 4
7	Din5	Digital input 5
8	Din6	Digital input 6
9	Din7	Digital input 7
10	Dout0	Digital output 0
11	Dout1	Digital output 1
12	Dout2	Digital output 2
13	Dout3	Digital output 3

X5	Hall and inc. encoder	
1	res.	Reserved
2	GND	Ground for sensor supply Notice: don't connect with system GND
3	Erw5	mcSPI expansion signal 5
4	+U5V	5V output voltage for sensor supply Sensors: encoder, hall
5	Erw3	mcSPI expansion signal 3
6	Inx	Inc. encoder, index channel
7	Erw4	mcSPI expansion signal 4
8	/B	Inc. encoder, B channel inverted
9	SpiMISO	mcSPI Master In
10	B	Inc. encoder, B channel
11	Spi/SS	mcSPI Slave Select
12	/A	Inc. encoder, A channel inverted
13	SpiMOSI	mcSPI Master Out
14	A	Inc. encoder, A channel
15	SpiCLK	mcSPI Clock
16	H3	Hall sensor 3
17	Erw1	mcSPI expansion signal 1
18	H2	Hall sensor 2
19	Erw2	mcSPI expansion signal 2
20	H1	Hall sensor 1
X6	Motor	
1	Ma	Motor phase A
2	Ma	Motor phase A
3	Ma	Motor phase A
4	Ma	Motor phase A
5	Mb	Motor phase B
6	Mb	Motor phase B
7	Mb	Motor phase B
8	Mb	Motor phase B
9	Mc	Motor phase C
10	Mc	Motor phase C
11	Mc	Motor phase C
12	Mc	Motor phase C

Terminal assignment

X7	Node ID	
1	/ld6	Node-ID Bit 6 inverted
2	/ld5	Node-ID Bit 5 inverted
3	/ld7	Node-ID Bit 7 inverted
4	/ld4	Node-ID Bit 4 inverted
5	GND	Ground
6	GND	Ground
7	/ld2	Node-ID Bit 2 inverted
8	/ld1	Node-ID Bit 1 inverted
9	/ld3	Node-ID Bit 3 inverted
10	/ld0	Node-ID Bit 0 inverted

